



PRODUCT COMPLIANCE SCHEDULE

GLAZZ INDUSTRIES PTY. LTD.

ACN 133 797 529

2 Clarke Street, Guildford, NSW 2161, Australia.

This schedule identifies the Certified Product(s) on which the PAS-Mark and ID. Number may be used.

AS/NZS 2208:1996 Safety glazing materials in buildings
(Including Amendment 1)

Product Description	Plain Float and Patterned Laminated Safety Glass, includes toughened safety glass complying with AS/NZS 2208
Classification	Grade "A"
Nominal Glass Thickness	1. 6.38mm to 16.38mm Laminated Float Glass 2. 6.38mm to 12.38mm Toughened and Heat Strengthened, Laminated Safety Glass. 3. 6.38mm to 8.38mm Laminated Patterned Glass
Maximum Glass Size	2140 mm (W) x 2760 mm (L)
Glass Colours	Acid Etch, Blue, Bronze, Clear, Green, Grey and White
Glass Patterns	Aqualite, Cathedral, Flemish, Gluechip, Gothic, Kosciusko, Mislite, Roughcast, Satinlite, Seadrift, Spotswood, Staccato and Strata.
PVB Suppliers PVB Interlayer Thickness	DuPont, Sekisui and Solutia 0.38mm to 0.76mm Clear and Tinted PVB Interlayer

This schedule supersedes any previously issued schedule.

Assessment ID No: CSI-7077


Certification date: 15 November 2009

Issue date: 17 November 2009

Expiry date: 14 November 2010

Schedule No: S1-Rev1-2009-11

PAS-Mark


Azma Khan
Managing Director
Certification Solutions
International Pty Ltd

